Town of Bedford

New Hampshire

Fire Department (603) 472-3219 Fax (603) 472-4565

Street number (min. 4" numbers contrasting with background)

GENERAL

Bedford Safety Complex 55 Constitution Drive Bedford, NH 03110-6008 Email: safety@bedfordnh.org

Building Department Health Department (603) 472-3838 Fax (603) 472-4565

Bedford Fire Department New Commercial Occupancy Checklist

The following checklist is designed to assist owners, occupants, and contractors recognize the most commonly overlooked items prior to a final inspection. This is not an all-inclusive list, some of these items will not apply to every project. Please contact the Bedford Fire Department with any questions prior to scheduling your final inspection.

EMERGENCY BACKUP LIGHTS

☐ Double-Headed EBU lights provided throughout exit access

	Knox Box and keys	☐ Double-Headed EBU light provided in each restroom
]	Emergency Contacts	☐ Double-Headed EBU light provided inside and outside of every exi
	.pdf of building footprint submitted electronically	
]	Sprinkler, fire alarm, and electrical rooms labeled	
	Roof access labeled	
	Rooftop units labeled	ELEVATORS
		☐ Emergency phone dials correct phone number/address
IRE EXTINGUISHERS		\square All devices recall elevator to primary floor \downarrow
		Primary floor elevator lobby smoke recalls to secondary floor
	10 lb. ABC dry chemical extinguisher at every exit	☐ FD elevator key for Knox Box
	Extinguishers arranged to meet proper coverage and travel distance	☐ Elevator drop key/tamper box in elevator machine room
	Extinguisher monitoring system provided (where required)	☐ Heat detector in machine room shunts power
	Extinguisher signage	☐ State certificates in place
	Service tags attached to extinguishers	

Proper coverage in all areas Spot test devices Test tampers and flow devices from sprinkler system Test time to alarm received by dispatch NFPA 72 Test Report provided before final inspection FACP and Pull Stations keyed to Cat-30 Graphic Map of initiation devices hung next to Annunciator/FACP Programming Password and Instructions for disabling devices placed in FACP All devices labeled HVAC units exceeding 2000 CFM shut down upon fire alarm activation Lockout on Circuit Breaker Red exterior beacon installed above Knox Box Supervisory and Trouble Alarms notify emergency contacts, not FD Strobes remain on when system is silenced 120v single station smoke alarm installed in break rooms/kitchenettes **SPRINKLER SYSTEMS** Proper coverage in all areas Test time for waterflow alarm at FACP Test time for water at dry trip test 200 lb. underground report 200 lb. aboveground report Hydraulic design stickers on risers All valves labeled Lockout for air compressor Spare head cabinet and wrench FDC chained cap with strainer

FIRE ALARM SYSTEMS

Knox Padlock for PIV

COMMERCIAL KITCHENS

	Puff test – activation triggers FA, shunts makeup air/power/fuel
	Signage for manual pull stations
	K class extinguisher(s) provided